

CRN#

NATBLD#

SERIAL#

67271

69183

OPERATIONAL TEST/ELECTRIC AND STEAM

MODELRBH30E3FX
DIAG.....
WIRE SIZE.....12
HZ.....50
VOLTS.....240
CONTROL VOLT....220.
PHASE...3
PRESSURE.....
KILOWATTS...30
CAPACITY 104 PPH/BTU/HR

UL FILE # E39545

DAY/MONTH 15 / 3 2010VOLTS 240 AMPS 70.2 TOTAL WATTS 30KPRESSURE 40 DIFF 5HEATER VOLTS 240KW 30PH 3 HZ 50

Reimers Electra Steam, 4407 Matrinsburg, Pike
Clear Brook, Va. 22624 PH 540-662-3811 FAX: 540-665-8101

STEAM

HOT WATER

MAX. W.P. 100 (NAMEPLATE)
MIN. SAFETY VALVE CAP. 105 PPH

MAX. W.P. _____ PSIG
MAX. TEMP. _____ DEG F
MIN. SAFETY VALVE CAP _____ PPH OR BTU
(3412 X KW/)

HYDRO TEST OF COMPLETE BOILER

P.S.I.G. 100 BY OC DATE 3/15/10
LOW WATER CUTOFF _____ HI WATER CUTOFF _____

DIELECTRIC VOLTAGE- WITHSTAND TEST:

VOLTS 1200 SAT ☒ UNSAT _____ BY OC DATE 3/15/10 (IAW U.L. 834)

(CORRECTED/RETEST) _____ BY _____ DATE _____ CORRECTIVE ACTION _____

SAFETY VALVE

CAPACITY 423
LB PER HR.

OPERATIONAL
TEST ☒

APPEARANCE ☒
BLOWDOWN MAN ☒ AUTO _____
CONDENSATE TANK _____
CONDENSATE & PIPE, ECT _____
CONTROLS ☒
ELEMENT ☒
FEED WATER VALVES ☒
INSTRUCTION BOOK ☒
LEAK INSPECTION ☒
PAINT ☒
PANEL ☒
PIPES ☒
PRESSURE CONTROLS ☒
SHEET METAL ☒
STEAM VALVE ☒
STEAM GAUGE ☒
STRANIER ☒
WARNING TAGS ☒
WATER GAUGE FITTINGS ☒
WIRE TERMINALS TIGHT ☒
WIRING DIA. ☒
ELEMENT QTY. 2
ELEMENT VOLT/KW 240 15
JURISDICTION = VA.
FUEL =ELECTRIC


NAMEPLATE: O.P. 100 KW 30 VOLTS 240 PH 3 HZ 50

Representing Reimers Electra Steam, INC. BY(Print) David E Coffin DATE 3/15/10

Signature David E. Coffin

INITIAL & DATE OPERATING CONTROLS, SAFETY CONTROLS, SAFETY VALVE ON REVERSE SIDE UPON COMPLETION OF OPERATIONAL TEST PERFORMANCE
(REF: ASME CSD-1, CG-500)

10f2



0016781

Page: 1

Work Order Traveler

SCHEDULED START: 03/04/10

DUE DATE: 03/08/10

QUANTITY: ~~2.00~~ (1.00)

UNIT OF MEASUREMENT: EACH

ITEM NUMBER: **RBH30E3FX**DESCRIPTION: **BOILER RBH 30KW 240V 3PH 100#**

REVISION: 003

OPTION CODE:

MAKE FOR: I/M

PLANNER:

QTY	PART	DESCRIPTION	QTY	PART	DESCRIPTION
2	20654	BRACKET SOLENOID VALVE	2	04593	SCREW .25-20 X .75 HEX CAP PLA
2	04462	BUSHING .375 X .25 BRASS SB16	2	04760	SCREW 1/4"-20 X .75" PAN HEAD
2	04701	CARTON RB 30W 35L 28.75H SLOT	4	04447	SCREW 10-24 X .375 RND HEAD SL
1	02240	CONDUIT ALFLEX type SWA .375"	16	01291	SCREW 8-32X.25RNDHD SLT MCH ZI
2	03844	CONDUIT CONNECTOR .375" DUPLEX	20	01246	SCREW 8-32X.375RDHD MCH PLT SL
2	02252	CONDUIT CONNECTOR .375"STR UL	8	01579	SCREW 8-32X1RND SLT PLATED STL
4	02266	CONDUIT SLEEVE .375" REDEYE	2	03262	STRAINER .375" Y
2	02254	CONNECTOR .375" 2 SCREW NEER	2	04731	STUD PRESS-IN THREADED .25"-20
2	02539	CONTACTOR 75A 120V 3P UL/CSA	2	RB30-SUBAS	SUBASSEMBLY RB 10 THRU 30 BOIL
2	20838	CONTROLLER 04316-EBC-LED	2	02176	TERMINAL LUG #8 HOMAC UL/CSA
2	03760	COPPER TUBE REF.5"ODX.032WALL	12	04080	TERMINAL RING FOR # 8 AWG WIR
2	04781	COUPLING .5" BRASS B16.15 125	2	02475	TRANSFORMER .25KVA B WALL MT48
2	20775-11	COVER ELEMENT TERMINALS RB REV	2	03346	VALVE BALL .5" W/LATCH 200 SWP
2	20775-7	COVER RIGHT ELEC BOX RB REV3	2	02325	VALVE GLOBE .375"125#SWP H.WHE
2	04229	DECAL SHEET	2	02637	VALVE SAFETY .5" 100# SWP 1" <i>OC 3/15/10</i>
2	04813	DINCONNECTOR/CORD FOR RB BOILE	2	04761	VALVE SOLENOID .375" 120V WATE
2	03923	ELBOW .5" TUBE X .375" NPT	8	03720	WASHER FOR PUMP RUBBER BUMPERS
2	04264	ELBOW CONNECTOR .5" TUBE X .37	5	03258	WIRE #14 STRND TEW 600 BLACK
2	04265	ELBOW STREET .375 NPT POLYPROP	1	02963	WIRE #14 TEW STRD 105C 600 GRE
-4	04164	ELEMENT 208V 10KW 3PH B-DIM.=1	36	04440	WIRE #8 TEFLON INS. W/GLASS SL
4	04253	ELEMENT 240V 15KW 3PH B-DIM=18	8	02744	WIRE NUT IDEAL UL/CSA
4	04574	FUSE 250V 3 AMP UL/CSA	3	04186	WIRE STRD #18 TEW (16/30) BLAC
-2	02655	FUSE 250V 5A UL/CSA	3	04187	WIRE STRD #18 TEW (16/30) WHIT
2	20863	LABEL MAX. TORQUE 50. LB IN /0			
2	20860	LABEL MAX. TORQUE 7.0 LB IN /0			
2	04301	LABEL NAMEPLATE UL/CSA 3.48 X			
4	03077	LOCKWASHER .25" HEAVY STEEL HE	2		
4	03561	LOCKWASHER 3/16" EXTERNAL TOOT	4		
2	20840	MANIFOLD FEED WATER SUBASSY RB			
2	04668	NIPPLE .25" X 1.125" BRASS SCH			
2	04635	NIPPLE .375 X 2" BRASS SB43 GR			
4	03948	NIPPLE .375 X CLOSE BRASS SCH4			
2	04784	NIPPLE .375" X 4" BRASS ASTM B			
2	04787	NUT .25-20 ZINC PLATED			
4	01351	NUT .25-20HEX JAM PLATE			
2	ORF-30	ORIFICE DRILLED #B (.236) FOR			
2	04163	PRESSURE CONTROL 60# OPERATING <i>OC 3/15/10</i>			
2	04296	PRESSURE CONTROL 90# HI LIMIT <i>OC 3/15/10</i>			
2	20842	PRESSURE CONTROL MANIFOLD RB R			
2	04661	PRESSURE GAUGE 2.0" .25" 0-160			
2	04178	PUMP 120V 1PH W/CORD POSITIVE			
2	20775-9	PUMP BASE MOUNTING BRACKET			
2	20775-8	PUMP BASE SOL VAL. RB REV3 ASS			

OPT1025*Fuse Block 2 poles CC class**Fuse 2.5A 600V CC class*