

CRN# _____

NATBLD# _____

SERIAL# 67507 69422

OPERATIONAL TEST/ELECTRIC AND STEAM

UL FILE # E39545

MODELRBH30J3F
DIAG.....
WIRE SIZE...12
HZ.....50
VOLTS.....415
CONTROL VOLT....220.
PHASE...3
PRESSURE.....40
KILOWATTS...30
CAPACITY 104 PPH/BTU/HR

DAY/MONTH 14/6 20010VOLTS 415 AMPS 24.1 TOTAL WATTS 30KPRESSURE 40 DIFF 5HEATER VOLTS 415KW 30PH 3 HZ 50

Reimers Electra Steam, 4407 Matrinsburg, Pike
Clear Brook, Va. 22624 PH 540-662-3811 FAX: 540-665-8101

APPEARANCE ☒BLOWDOWN MAN ☒ AUTO _____

CONDENSATE TANK _____

CONDENSATE & PIPE, ECT _____

CONTROLS ☒ELEMENT ☒FEED WATER VALVES ☒INSTRUCTION BOOK ☒LEAK INSPECTION ☒PAINT ☒PANEL ☒PIPES ☒PRESSURE CONTROLS ☒SHEET METAL ☒STEAM VALVE ☒STEAM GAUGE ☒STRANIER ☒WARNING TAGS ☒WATER GAUGE FITTINGS ☒WIRE TERMINALS TIGHT ☒WIRING DIA. ☒ELEMENT QTY. 2ELEMENT VOLT/KW 240/15

JURISDICTION = VA.

FUEL =ELECTRIC

STEAM

HOT WATER

MAX. W.P. 100 (NAMEPLATE)
MIN. SAFETY VALVE CAP. 10.5 PPH

MAX. W.P. _____ PSIG
MAX. TEMP. _____ DEG F
MIN. SAFETY VALVE CAP _____ PPH OR BTU
(3412 X KW/_____)

HYDRO TEST OF COMPLETE BOILER

P.S.I.G. 100 BY DC DATE 6/14/10
LOW WATER CUTOFF _____ HI WATER CUTOFF _____

DIELECTRIC VOLTAGE- WITHSTAND TEST:

VOLTS 2200 SAT ☒ UNSAT _____ BY DC DATE 6/14/10 (IAW U.L. 834)

(CORRECTED/RETEST) _____ BY _____ DATE _____ CORRECTIVE ACTION _____

SAFETY VALVE

CAPACITY 423
LB PER HR.

OPERATIONAL
TEST ☒

NAMEPLATE: O.P. 100 KW 30 VOLTS 415 PH 3 HZ 50


Representing Reimers Electra Steam, INC. BY (Print) David E. Coffey DATE 6/14/10

Signature David E Coffey

INITIAL & DATE OPERATING CONTROLS, SAFETY CONTROLS, SAFETY VALVE ON REVERSE SIDE UPON COMPLETION OF OPERATIONAL TEST PERFORMANCE

(REF: ASME CSD-1, CG-500)

10F2



0017472

Work Order Traveler

SCHEDULED START: 06/08/10

DUE DATE: 06/10/10

ITEM NUMBER: RBH30J3F

QUANTITY: 2.00

DESCRIPTION: BOILER RBH 30KW 415V 3PH 100#

UNIT OF MEASUREMENT: EACH

REVISION: 003

OPTION CODE:

MAKE FOR: I/M

PLANNER:

QTY	PART	DESCRIPTION	QTY	PART	DESCRIPTION
2	20654	BRACKET SOLENOID VALVE	2	04760	SCREW 1/4"-20 X .75" PAN HEAD
2	04462	BUSHING .375 X .25 BRASS SB16	4	04447	SCREW 10-24 X .375 RND HEAD SL
2	04701	CARTON RB 30W 35L 28.75H SLOT	16	01291	SCREW 8-32X.25RNDHD SLT MCH ZI
1	02240	CONDUIT ALFLEX type SWA .375"	20	01246	SCREW 8-32X.375RDHD MCH PLT SL
2	03844	CONDUIT CONNECTOR .375" DUPLEX	8	01579	SCREW 8-32X1RND SLT PLATED STL
2	02252	CONDUIT CONNECTOR .375"STR UL	2	03262	STRAINER .375" Y
4	02266	CONDUIT SLEEVE .375" REDEYE	2	04731	STUD PRESS-IN THREADED .25"-20
2	02530	CONTACTOR 50A 120V 3P UL/CSA	2	RB30-SUBAS	SUBASSEMBLY RB 10 THRU 30 BOIL
2	20838	CONTROLLER 04316-EBC-LED	2	02176	TERMINAL LUG #8 HOMAC UL/CSA
2	03760	COPPER TUBE REF.5"ODX.032WALL	12	04080	TERMINAL RING FOR # 8 AWG WIR
2	04781	COUPLING .5" BRASS B16.15 125	12	04183	TERMINAL RING #12-10 WIRE #8 S
2	20775-11	COVER ELEMENT TERMINALS RB REV	2	02475	TRANSFORMER .25KVA B WALL MT48
2	20775-7	COVER RIGHT ELEC BOX RB REV3	2	03346	VALVE BALL .5" W/LATCH 200 SWP
2	04229	DECAL SHEET	2	02325	VALVE GLOBE .375"125#SWP H.WHE
2	04813	DINCONNECTOR/CORD FOR RB BOILE	2	02637	VALVE SAFETY .5" 100# SWP 1" O
2	03923	ELBOW .5" TUBE X .375" NPT	2	04761	VALVE SOLENOID .375" 120V WATE
2	04264	ELBOW CONNECTOR .5" TUBE X .37	8	03720	WASHER FOR PUMP RUBBER BUMPERS
2	04265	ELBOW STREET .375 NPT POLYPROP	36	04278	WIRE #10 TEFLON INS. W/GLASS S
-4	04164	ELEMENT 208V 10KW 3PH B-DIM.=1	5	03258	WIRE #14 STRND TEW 600 BLACK
4	04253	ELEMENT 240V 15KW 3PH B-DIM=18	1	02963	WIRE #14 TEW STRD 105C 600 GRE
4	04574	FUSE 250V 3 AMP UL/CSA	8	02744	WIRE NUT IDEAL UL/CSA
-2	02655	FUSE 250V 5A UL/CSA	3	04186	WIRE STRD #18 TEW (16/30) BLAC
2	02140	FUSE BLOCK 250V 30A 1P UL/CSA	3	04187	WIRE STRD #18 TEW (16/30) WHIT
4	04768	GAUGE ROD .1875" X 7"			
2	20862	LABEL MAX. TORQUE 40. LB IN /0			
2	20860	LABEL MAX. TORQUE 7.0 LB IN /0			
2	04301	LABEL NAMEPLATE UL/CSA 3.48 X			
4	03077	LOCKWASHER .25" HEAVY STEEL HE			
4	03561	LOCKWASHER 3/16" EXTERNAL TOOT			
2	20840	MANIFOLD FEED WATER SUBASSY RB			
2	04668	NIPPLE .25" X 1.125" BRASS SCH			
4	03948	NIPPLE .375 X CLOSE BRASS SCH4			
2	04784	NIPPLE .375" X 4" BRASS ASTM B			
2	04787	NUT .25-20 ZINC PLATED			
4	01351	NUT .25-20HEX JAM PLATE			
2	ORF-30	ORIFICE DRILLED #B (.236) FOR			
2	04163	PRESSURE CONTROL 60# OPERATING			
2	04296	PRESSURE CONTROL 90# HI LIMIT			
2	20842	PRESSURE CONTROL MANIFOLD RB R			
2	04661	PRESSURE GAUGE 2.0" .25" 0-160			
2	04178	PUMP 120V 1PH W/CORD POSITIVE			
2	20775-9	PUMP BASE MOUNTING BRACKET			
2	20775-8	PUMP BASE SOL VAL. RB REV3 ASS			
2	04593	SCREW .25-20 X .75 HEX CAP PLA			