

CRN#

NATBLD#

SERIAL#

68124

70043

MODELRBH30K3F
WIRE DIAG.....W
WIRE SIZE.....12
HZ.....60
VOLTS.....480
CONTROL VOLT....120.
PHASE.....3
PRESSURE.....80
KILOWATTS...30
CAPACITY 104 PPH/BTU/HR

OPERATIONAL TEST/ELECTRIC AND STEAM

UL FILE # E39545

DAY/MONTH 7 / 12 20010
VOLTS 480 AMPS 18.2 TOTAL WATTS 30K
PRESSURE 80 DIFF 5

Amps TESTED ON 240V
Reimers Electra Steam, 4407 Matrinsburg, Pike
Clear Brook, Va. 22624 PH 540-662-3811 FAX: 540-665-8101

HEATER VOLTS 480KW 30PH 3 HZ 60

TEAM

HOT WATER

MAX. W.P. 100 (NAMEPLATE)
MIN. SAFETY VALVE CAP. 105 PPH

MAX. W.P. _____ PSIG
MAX. TEMP. _____ DEG F
MIN. SAFETY VALVE CAP _____ PPH OR BTU
(3412 X KW/)

HYDRO TEST OF COMPLETE BOILER

P.S.I.G. 100 BY OC DATE 12/7/10
LOW WATER CUTOFF _____ HI WATER CUTOFF _____

SAFETY VALVE

CAPACITY 423
LB PER HR.

OPERATIONAL
TEST ✓

DIELECTRIC VOLTAGE- WITHSTAND TEST:

VOLTS 2350 SAT ✓ UNSAT _____ BY OC DATE 12/7/10 (IAW U.L. 834)

(CORRECTED/RETEST) _____ BY _____ DATE _____ CORRECTIVE ACTION _____

NAMEPLATE: O.P. 100 KW 30 VOLTS 480 PH 3 HZ 60

Representing Reimers Electra Steam, INC. BY(Print) David E. Cofer DATE 12/7/10

Signature David E. Cofer

APPEARANCE

BLOWDOWN MAN _____ AUTO _____
CONDENSATE TANK _____
CONDENSATE & PIPE, ECT _____
CONTROLS _____
ELEMENT _____
FEED WATER VALVES _____
INSTRUCTION BOOK _____
LEAK INSPECTION _____
PAINT _____
PANEL _____
PIPES _____
PRESSURE CONTROLS _____
SHEET METAL _____
STEAM VALVE _____
STEAM GAUGE _____
STRANIER _____
WARNING TAGS _____
WATER GAUGE FITTINGS _____
WIRE TERMINALS TIGHT _____
WIRING DIA. _____
ELEMENT QTY. _____
ELEMENT VOLT/KW _____
JURISDICTION = VA.
FUEL =ELECTRIC

INITIAL & DATE OPERATING CONTROLS, SAFETY CONTROLS, SAFETY VALVE ON REVERSE SIDE UPON COMPLETION OF OPERATIONAL TEST PERFORMANCE
(REF: ASME CSD-1, CG-500)

30f3



0018739

Page: 1

Work Order Traveler

SCHEDULED START: 11/29/10

DUE DATE: 12/02/10

QUANTITY: ~~300~~ 100

UNIT OF MEASUREMENT: EA

ITEM NUMBER: **RBH30K3F**DESCRIPTION: **BOILER RBH 30KW 480V 3PH 100#**

REVISION: 003

OPTION CODE:

MAKE FOR: I/M

PLANNER:

QTY	PART	DESCRIPTION	QTY	PART	DESCRIPTION
3	20654	BRACKET SOLENOID VALVE	3	04731	STUD PRESS-IN THREADED .25"-20
3	04462	BUSHING .375 X .25 BRASS SB16	3	RB30-SUBAS	SUBASSEMBLY RB 10 THRU 30 BOIL
3	04701	CARTON RB 30W 35L 28.75H SLOT	18	04080	TERMINAL RING FOR # 8 AWG WIR
3	02254	CONNECTOR .375" 2 SCREW NEER	18	02741	TERMINAL RING 10-12WIRE #10STU
3	02530	CONTACTOR 50A 120V 3P UL/CSA	3	03818	TICKET HOLDER FOR SHOP CLEAR F
3	20838	CONTROLLER 04316-EBC-LED	3	03346	VALVE BALL .5" W/LATCH 200 SWP
3	03760	COPPER TUBE REF.5"ODX.032WALL	3	02325	VALVE GLOBE .375"125#SWP H.WHE
3	04781	COUPLING .5" BRASS B16.15 125	3	02637	VALVE SAFETY .5" 100# SWP 1" O
3	20775-11	COVER ELEMENT TERMINALS RB REV	3	04761	VALVE SOLENOID .375" 120V WATE
3	20775-7	COVER RIGHT ELEC BOX RB REV3	12	03720	WASHER FOR PUMP RUBBER BUMPERS
3	04229	DECAL SHEET	30	04278	WIRE #10 TEFLON INS. W/GLASS S
3	04813	DINCONNECTOR/CORD FOR RB BOILE			
3	03923	ELBOW .5" TUBE X .375" NPT			
3	04264	ELBOW CONNECTOR .5" TUBE X .37			
3	04265	ELBOW STREET .375 NPT POLYPROP			
-6	04164	ELEMENT 208V 10KW 3PH B-DIM.=1			
6	04666	ELEMENT 480V 15KW 3P BDIM 18.5			
3	02655	FUSE 250V 5A UL/CSA			
3	20862	LABEL MAX. TORQUE 40. LB IN /0			
3	20860	LABEL MAX. TORQUE 7.0 LB IN /0			
3	04301	LABEL NAMEPLATE UL/CSA 3.48 X			
6	03077	LOCKWASHER .25" HEAVY STEEL HE			
6	03561	LOCKWASHER 3/16" EXTERNAL TOOT			
3	20840	MANIFOLD FEED WATER SUBASSY RB			
3	04668	NIPPLE .25" X 1.125" BRASS SCH			
6	03948	NIPPLE .375 X CLOSE BRASS SCH4			
3	04784	NIPPLE .375" X 4" BRASS ASTM B			
3	04787	NUT .25-20 ZINC PLATED			
6	01351	NUT .25-20HEX JAM PLATE			
3	04163	PRESSURE CONTROL 60# OPERATING			
3	04296	PRESSURE CONTROL 90# HI LIMIT			
3	20842	PRESSURE CONTROL MANIFOLD RB R			
3	04661	PRESSURE GAUGE 2.0" .25" 0-160			
3	04178	PUMP 120V 1PH W/CORD POSITIVE			
3	20775-9	PUMP BASE MOUNTING BRACKET			
3	20775-8	PUMP BASE SOL VAL. RB REV3 ASS			
3	04593	SCREW .25-20 X .75 HEX CAP PLA			
3	04760	SCREW 1/4"-20 X .75" PAN HEAD			
6	04447	SCREW 10-24 X .375 RND HEAD SL			
24	01291	SCREW 8-32X.25RNDHD SLT MCH ZI			
30	01246	SCREW 8-32X.375RDHD MCH PLT SL			
12	01579	SCREW 8-32X1RND SLT PLATED STL			
3	03262	STRAINER .375" Y			